



Concentrate 1:20

EXTREME® ULTRA



Ultra Concentrated • Low Odor Floor Stripper

This high power, high productivity floor stripper is an ultra concentrated formula that provides the lowest end-use cost per gallon for superior economy. It penetrates and removes multiple coats of burnished finish with minimum labor. The low odor formula is pleasant to use and is ideal for use in supermarkets and other 24 hour operations where odors are a concern. With ultimate stripping power, this product works quickly, strips floors completely on the first pass and requires no rinsing.



Uses

Use to remove finishes and sealers:

- Acrylic
- Water-based urethane
- Copolymer
- Metal crosslinked
- Oligomer
- Polymer
- Styrene
- Thermoplastics

NOTE: This product should not be used on wood floors or painted surfaces. Not recommended for use on linoleum, asphalt tile or rubber tile floors since bleaching or softening may occur. DO NOT DILUTE WITH HOT WATER.

Features

- **Low end-use cost** – Powerful, fast acting formula uses less product and works more quickly to lower overall costs.
- **Ultra concentrated** – Less packaging to dispose.
- **“Point of Use” dilution control** – Quart package makes it easy to measure and simple to use. One quart makes 5 gallons of stripping solution.
- **Low odor** – Reduces unpleasant and obnoxious stripping odors. Ideal for use in facilities that are sensitive to odors.
- **Labor Saving** – Reduces labor by requiring a minimum initial contact time, and the powerful formula cuts through build-ups quickly and completely.
- **Rinse Free** – Requires no neutralization or flood rinsing. With lower pH, this product is ideal for use on many natural stone and marble surfaces. Free of harsh caustics and ammonia.

Properties

Color	Clear, slightly amber
Flash point.....	None
Fragrance.....	Pleasant
Freeze/thaw stability	N/A
pH	11.9
pH @ dilution	11.2
Residue on drying.....	None
Shelf life.....	1 year
Caustics	None

Authorized Betco Distributor

Directions For Use

Read the entire label before using this product.

Use for removing multiple coats of water-based acrylic and urethane fortified floor finishes and sealers from resilient tile (vinyl composition, vinyl), concrete, marble, terrazzo, and quarry. Do not use on asphalt tile, wood, linoleum, sheet vinyl, rubber tile or painted surfaces. Test in an inconspicuous area first.

1. Fill bucket from long hose on dispenser.
2. Set up “Wet Floor” signs in areas to be stripped.
3. Apply solution liberally and allow 3-5 minutes contact time. Keep floor wet at all times.
4. Agitate solution, remove and thoroughly rinse.

Safety

Keep out of reach of children. For institutional and commercial use. **DANGER: CORROSIVE.** Causes burns. Vapors harmful. Harmful if swallowed. Contains 2-Butoxyethanol and Monoethanolamine. Avoid contact with skin and eyes. Wear chemical anti-splash goggles and suitable gloves and boots. **FIRST AID:** Remove contaminated clothing immediately. **SKIN AND EYES:** Flush skin and eyes immediately with large quantities of water for at least 15 minutes. Seek immediate medical attention. **INGESTION:** If swallowed, contact a poison control center immediately for treatment advice. Have conscious person take sips of water if able to swallow. Never give anything by mouth to an unconscious person. Do not induce vomiting unless instructed to do so by poison control center or doctor. **INHALATION:** Remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration.

Available In

- Case/12 - Quarts (946 mL): Item #19412-00
- Case/4 - 1 Gallon (3.78 L): Item #19404-00
- Pail/5 Gallon (18.9 L): Item #19405-00
- Drum/55 Gallon (208 L): Item #19455-00
- FASTDRAW® SYSTEM Case/4 - 2 L Bottles: Item #19447-00
- GREEN EARTH® II SYSTEM
- Case/2 - 4 L Boxes: Item #19437-00

C1030 - Floor Care - Strippers

11.11

