



# SS GYM COAT



## Water-Based • High Traffic Wood Floor Finish

This water-based two component wood floor finish is formulated especially for high traffic wood floors. It provides a clear finish that remains unmatched in performance and durability. It outwears all other types of wood floor finishes with the fastest curing time on the market. Sports floors can be coated and ready for activities the next day. It also contains a special UV inhibitor that provides even more protection from the sun's harmful rays.



### Uses

- Sports floors – Gymnasiums, aerobic and exercise floors
- Commercial – Offices, assembly halls, retail, classrooms

### Benefits

- MFMA approved.
- Fast curing (play the next day).
- Fast drying – Dries in 2 - 3 hours and must be recoated within 6 hours.
- Highest durability – So durable it stands up to warehouse forklift traffic.
- Low odor – No lingering solvent odors for constant use facilities.
- Dries clear – No discoloration of line markings and logos.
- Easy clean up – Just use water, no solvents.
- UV inhibitor minimizes sunlight related color changes.

### Properties

Color (dried).....	Crystal Clear
Color (liquid).....	Milky White
Coverage.....	600 - 750 sq.ft./gal.
Dry time.....	2 - 3 hrs. between coats
Recoat time.....	Recoat within 24 hrs.
Pot life.....	24 hrs.
Flash point.....	Greater than 200° F
Freeze/thaw stability.....	3 cycles
Rubber burn resistance.....	Excellent
Viscosity.....	40 - 60 centipoise
Weight per gallon.....	8.75 lbs.
VOC.....	<350 g/L
Shelf life.....	1 year

### Available In

Case/4 - 1 Gallon (3.78 L): Item #68004-00  
 Pail/5 Gallon (18.9 L): Item #68005-00



National  
Wood Flooring  
Association  
Member

### Directions For Use

Read the entire label before using this product.

**PREPARATION: FOR NEW OR SANDED FLOORS:** Prepare the floor using accepted MFMA procedures. Vacuum all dust and tack with cotton towel. Apply water-based wood sealer following instructions on sealer label: 2 coats minimum. **FOR SCREENING AND RECOATING:** Always clean the floor prior to screening. Mix wood floor maintenance cleaner at 32 oz./gal. or 250 mL/L (1:4) with water and tack using a clean towel. Screen using new 120 or 150 grit screens, vacuum and tack using a water moistened cotton towel. **APPLICATION:** Shake or mix container before opening. While stirring product, add catalyst slowly and continue mixing for 30 seconds. Mix thoroughly and let stand for 5 minutes. Once catalyzed, pot life is 24 hours. Apply at 600 - 750 sq.ft./gal. Allow to dry thoroughly (minimum 2 - 3 hours between coats depending on conditions with a maximum of 24 hours). Abrade between coats if 24 hours has elapsed with a maroon top scrub pad or 150 grit screen. Apply 1 - 2 coats minimum. Allow normal traffic after 24 hours. *NOTE: Allow adequate ventilation. Circulate air above the floor or place fans to pull moisture away from the floor. Allow adequate airflow for at least 24 hours after final coat is applied. Use air conditioners and exhaust fans where available.* **MAINTENANCE: DAILY MAINTENANCE:** Dust mop using water-based dust mop treatment (see product label for additional instructions). Dust mop as often as possible, at least once per day. **WEEKLY MAINTENANCE:** Tack (deep clean) the floor using wood floor maintenance cleaner (see product label for additional instructions). Tack frequently, but at least once a week. *Refer to the Water-Based Wood Coatings Application & Procedure Guide for detailed instructions.* **NOTE: Slip resistance meets or exceeds (ASTM D 2047-04) James Machine 0.5 minimum.**

### Safety

Keep out of reach of children. For industrial and commercial use. **WARNING: VAPOR HARMFUL. VAPORS MAY CAUSE DROWSINESS AND DIZZINESS. HARMFUL IF SWALLOWED. IRRITATING TO EYES. IRRITATING TO SKIN. HARMFUL IF ABSORBED THROUGH SKIN.** Use with adequate ventilation. Do not breathe vapor, mist, or dust. Ensure fresh air entry during and after application. Wearing an appropriate, properly fitted respirator (NIOSH approved) during and after application is recommended unless air monitoring demonstrates vapor/mist levels are below applicable limits. Follow manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Keep closures tight and upright to prevent leakage. Keep container closed. In case of spillage, absorb and dispose of in accordance with local applicable regulations. **FIRST AID: IF ON SKIN OR CLOTHING:** Remove contaminated clothing, wash skin with soap and water. Seek medical attention if irritation persists. **IF IN EYES:** Rinse with gentle stream of water for 15 minutes. Seek medical attention. **IF INHALED:** Remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration. **IF SWALLOWED:** Contact a poison control center or doctor for treatment advice. Do NOT induce vomiting unless instructed to do so by poison control center or doctor.

Literature Item #68092-92

