



Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200

| | | |
|---------------------------|---|---|
| | WHMIS Class E: Corrosive liquid. | HCS CLASS: Toxic. HCS CLASS: Corrosive liquid. |
| WHMIS (Pictograms) | WHMIS (Classification) | HCS |

Section 1. Chemical Product and Company Identification

| | | | |
|-------------------------------------|--|---------------------------------|-------------------------|
| Product Name/ Trade name | AX-It | Code | 099 |
| Synonym | Baseboard Cleaner and Stripper | CAS # | Not applicable. |
| Chemical Family | Not available. | Validation Date | 3/2/2007 |
| Chemical Formula | Not applicable. | Print Date | 3/23/2007 |
| Manufacturer/ Supplier | Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607 (419) 241-2156 | In Case of Emergency | Chemtrec (800) 424-9300 |
| TSCA | TSCA Inventory: All components listed or are exempt from listing. | | |
| DSL/ NDSL | All components listed unless noted elsewhere on this MSDS | | |
| | | Protective Clothing | |

Section 2. Composition and Information on Ingredients

| Name | CAS # | % by Weight | Exposure Limits | LC ₅₀ /LD ₅₀ |
|-------------------------|------------|-------------|---|--|
| Water | 7732-18-5 | 0-100 | Not available. | Not available. |
| 2-Butoxyethanol | 111-76-2 | 10-15 | TWA: 25 (ppm) TWA: 50 (ppm) from OSHA (PEL) | ORAL (LD50): Acute: 1746 mg/kg [Rat]. GAS (LC50): Acute: 926 ppm 4 hour(s) [Mouse]. |
| Monoethanolamine | 141-43-5 | 5-10 | TWA: 3 (ppm) TWA: 6 (ppm) from OSHA (PEL)STEL: 6 (ppm) | Not available. |
| Liquified Petroleum Gas | 68476-85-7 | 5-10 | TWA: 1000 (ppm) TWA: 1000 (ppm) from OSHA (PEL) | Not available. |
| Xanthan Gum | 11138-66-2 | 0-5 | Not available. | ORAL (LD50): Acute: 5000 mg/kg [Rat]. |
| Ethylene Glycol | 107-21-1 | 0-5 | Not available. | Not available. |
| Sodium Benzoate | 532-32-1 | 0-5 | Not available. | Not available. |
| Perfume Oil | N/A | 0-5 | Not available. | Not available. |

Section 3. Hazards Identification

| | |
|---|--|
| Potential Acute Health Effects | Corrosive to eyes and skin. Irritating to nose, throat and mouth. |
| Potential Chronic Health Effects | Prolonged exposure may result in skin burns and ulcerations. Severe over-exposure can produce choking, unconsciousness. May aggravate existing respiratory conditions such as asthma. The following information is applicable to animal data and relevance to humans has yet to be determined: Repeated or prolonged exposure to the substance can produce kidney damage.(Monoethanolamine, 2-Butoxyethanol) Repeated or prolonged exposure to the substance can produce blood disorders. (2-butoxyethanol) |

Carcinogenic Effects

Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First Aid Measures

| | |
|---------------------|---|
| Eye Contact | Avoid contact with eyes. Flush eyes with a gentle stream of water holding eyelids open for at least 15 minutes. Seek immediate medical attention. |
| Skin Contact | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately. |
| Inhalation | Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible. |
| Ingestion | Call a poison control center immediately for treatment advice. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person |

Section 5. Fire Fighting Measures

| | |
|---|------------------------|
| Products of Combustion | Not available. |
| Fire Fighting Media and Instructions | N/A |
| Special Remarks on Fire Hazards | N/A |
| Special Remarks on Explosion Hazards | Heated cans may burst. |

Section 6. Accidental Release Measures

| | |
|---|---|
| Small Spill and Leak | Absorb with an inert material and place in an appropriate waste disposal container. |
| Large Spill and Leak | Absorb with an inert material and put the spilled material in an appropriate waste disposal. |
| Personal Protection in Case of a Large Spill | Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product. |

Section 7. Handling and Storage

| | |
|------------------------|--|
| Precautions | Avoid contact with skin and eyes. COMBUSTIBLE LIQUID AND VAPOR. DO NOT ingest. |
| Incompatibility | Strong acids and oxidizers. |
| Storage | Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of reach of children. For Institutional and Commercial Use |

Section 8. Exposure Controls/Personal Protection

Engineering Controls Good general ventilation should be sufficient to control airborne levels.


Personal Protection

Eyes Splash goggles.

Body Long Pants and Long Sleeves to avoid skin contact.

Respiratory Wear appropriate respirator when ventilation is inadequate.

Hands Gloves (impervious).

Protective Clothing (Pictograms)

Exposure Limits**2-Butoxyethanol**

TWA: 25 (ppm)

TWA: 50 (ppm) from OSHA (PEL)

Monoethanolamine

TWA: 3 (ppm)

TWA: 6 (ppm) from OSHA (PEL)

STEL: 6 (ppm)

Liquified Petroleum Gas

TWA: 1000 (ppm)

TWA: 1000 (ppm) from OSHA (PEL)

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

| | | | |
|--|---|--------------|-----------------|
| Physical State and Appearance | Liquid. | Odor | Characteristic. |
| Molecular Weight | Not applicable. | Taste | Not available. |
| pH | 11.5 to 12.5 [Basic.] | Color | Clear |
| Boiling/Condensation Point | N/A | | |
| Melting/Freezing Point | Not available. | | |
| Critical Temperature | Not available. | | |
| Instability Temperature | Not available. | | |
| Specific Gravity | Not available. | | |
| Vapor Pressure | 60 psig @ 68°F | | |
| Vapor Density | >1 (Air = 1) | | |
| Volatility | 99 | | |
| VOC | Not available. | | |
| Evaporation Rate | <1 | | |
| Dispersion Properties | See solubility in water. | | |
| Solubility | Easily soluble in cold water. | | |
| The Product is: | May be combustible at high temperature. | | |
| Auto-ignition Temperature | Not available. | | |
| Flash Points | Not available. | | |
| Flammable Limits | LOWER: 1.1% UPPER: 17% | | |
| Fire Hazards in Presence of Various Substances | No specific information is available in our database regarding the flammability of this product in presence of various materials. | | |
| Explosion Hazards in Presence of Various Substances | Containers may explode when heated. | | |

Section 10. Stability and Reactivity Data

| | |
|---|-----------------------------|
| Stability | The product is stable. |
| Incompatibility with Various Substances | Strong acids and oxidizers. |
| Hazardous Decomposition Products | Will not occur. |

Section 11. Toxicological Information

| | |
|--|--|
| Routes of Entry | Absorbed through skin. Eye contact. Inhalation. Ingestion. |
| Toxicity to Animals | WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol). Acute toxicity of the gas (LC50): 926 ppm 4 hour(s) [Mouse]. (2-Butoxyethanol). |
| Acute Effects on Humans | <i>Eyes</i> Severe eye irritant. Liquid and mist may damage the eyes, causing corneal injury. <i>Skin</i> Severe skin irritant. May cause redness, swelling, and defatting. <i>Inhalation</i> Vapors may be irritating to mucous membranes of the nose, throat, and lungs. High concentrations may cause headache, dizziness, and nausea. <i>Ingestion</i> May cause dizziness, headache, nausea, vomiting, and diarrhea. Harmful if swallowed. |
| Chronic Effects on Humans | Prolonged exposure may result in skin burns and ulcerations. Severe over-exposure can produce choking, unconsciousness. May aggravate existing respiratory conditions such as asthma. The following information is applicable to animal data and relevance to humans has yet to be determined: Repeated or prolonged exposure to the substance can produce kidney damage.(Monoethanolamine, 2-Butoxyethanol) Repeated or prolonged exposure to the substance can produce blood disorders. (2-butoxyethanol) |
| Special Remarks on Toxicity to Animals | No additional remark. |
| Special Remarks on Chronic Effects on Humans | No additional remark. |

Section 12. Ecological Information


| | |
|---|---|
| Ecotoxicity | Not Available |
| BOD5 and COD | Not available. |
| Products of Biodegradation | Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. |
| Toxicity of the Products of Biodegradation | Not available. |
| Special Remarks on the Products of Biodegradation | No additional remark. |

Section 13. Disposal Considerations

| | |
|-------------------|--|
| Waste Information | Waste must be disposed of in accordance with federal, state and local environmental control regulations. |
| Waste Stream | Not available. |

Section 14. Transport Information

DOT (U.S.A)
(Pictograms)



TDG Classification Not controlled under TDG (Canada).




PIN UN, Proper Shipping Name, PG Not applicable.

Maritime Transportation Not available.

Special Provisions for Transport Not applicable.

Section 15. Other Regulatory Information and Pictograms

WHMIS (Classification) WHMIS Class E: Corrosive liquid.



Regulatory Lists No products were found.

Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications

HCS (U.S.A.) HCS CLASS: Toxic.
HCS CLASS: Corrosive liquid.

USA Regulatory Lists No components found on California Prop 65

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Butoxyethanol: immediate health hazard, delayed health hazard; Ethylene Glycol; Monoethanolamine; Fire; Liquefied Petroleum Gas
SARA 313 toxic chemical notification and release reporting: 2-Butoxyethanol; Ethylene Glycol


DSD (EEC)

International Regulations Lists No products were found.

Hazardous Material Information System (U.S.A.)

| | | |
|-----------------|---|---|
| Health | * | 3 |
| Flammability | | 1 |
| Physical Hazard | | 0 |

National Fire Protection Association (U.S.A.)



The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product. Specific Hazard

Section 16. Other Information

Validated by CRushton on 3/2/2007.

Verified by CRushton.

Printed 3/23/2007.

Information Contact Betco Corporation
1001 Brown Avenue
Toledo, Ohio 43607

Notice to Read:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 3/2/2007.

AX-It

Page: 6/6

Continued on Next Page