




Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200

	E	HCS CLASS: Toxic. HCS CLASS: Corrosive liquid.
WHMIS (Pictograms)	WHMIS (Classification)	HCS

Section 1. Chemical Product and Company Identification

Product Name/ Trade name	Super Kemite Mega Base	Code	554
Synonym	Heavy Duty Degreaser Concentrate	CAS #	Not applicable.
Chemical Family	Not available.	Validation Date	2/13/2009
Chemical Formula	Not applicable.	Print Date	2/13/2009
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Oh 43607 (419) 241-2156	In Case of Emergency	Chemtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS		
		Protective Clothing 	

Section 2. Composition and Information on Ingredients

Name	CAS #	% by Weight	Exposure Limits	LC ₅₀ /LD ₅₀
Sodium Metasilicate	6834-92-0	40 - 50	Not available.	Not available.
2-Butoxyethanol	111-76-2	20 - 30	ACGIH (United States). TWA: 20 ppm OSHA (United States). TWA: 50 ppm	ORAL (LD50): Acute: 1746 mg/kg [Rat].
Tetrasodium salt of ethylenediaminetetraacetic acid	64-02-8	10 - 15	Not available.	ORAL (LD50): Acute: 3030 mg/kg [Rat].
Sodium Tallate	61790-45-2	4 - 6	Not available.	Not available.
Anionic Surfactant	25155-30-0	1 - 5	Not available.	Not available.

Section 3. Hazards Identification

Potential Acute Health Effects	Corrosive to skin and eyes on contact. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Severe over-exposure can result in death.
Potential Chronic Health Effects	Prolonged exposure may result in skin burns and ulcerations. Severe over-exposure can produce lung damage, choking, unconsciousness or death. The amount of tissue damage depends on length of contact.
Carcinogenic Effects	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First Aid Measures

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Skin Contact	Corrosive to eyes and skin. Wash with plenty of soap and water. Remove contaminated clothing. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. Seek medical attention.
Ingestion	Do not induce vomiting. Have conscious person drink several glasses of water or milk. NEVER give an unconscious person anything to ingest. Seek immediate medical attention.

Section 5. Fire Fighting Measures

Products of Combustion	Not available.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.
Special Remarks on Fire Hazards	Not available.
Special Remarks on Explosion Hazards	Not available.

Section 6. Accidental Release Measures

Small Spill and Leak	Chemical anti-splash goggles. Absorb with an inert material and place in an appropriate waste disposal container.
Large Spill and Leak	Corrosive liquid. Stop leak if without risk. Use appropriate instruments to put the spilled material in a waste disposal. Prevent entry into sewers, basements or confined areas; dike if needed.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Section 7. Handling and Storage

Precautions	After handling, always wash hands thoroughly with soap and water. Avoid breathing vapors or spray mists. Avoid contact with skin and eyes. Keep out of reach of children.
Incompatibility	Strong acids. acids
Storage	Keep container dry. Keep in a cool place. Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of the reach of children. Not for use or storage in or around the home.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels.
Personal Protection	
<i>Eyes</i>	Splash goggles.
<i>Body</i>	Long Pants and Long Sleeves to avoid skin contact. No additional special protective clothing is required.
<i>Respiratory</i>	In case of insufficient ventilation, wear suitable respiratory equipment.
<i>Hands</i>	Gloves (impervious).

Protective Clothing (Pictograms)



Exposure Limits**2-Butoxyethanol**

TWA: 25 (ppm)

TWA: 50 (ppm) from OSHA (PEL) [United States]

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.	Odor	Pleasant.
Molecular Weight	Not applicable.	Taste	Not available.
pH	13 to 14 [Basic.]	Color	Violet.
Boiling/Condensation Point	215°F initial		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.06 (Water = 1)		
Vapor Pressure	20mm Hg @ 68°F		
Vapor Density	>1 (Air = 1)		
Volatility	80		
VOC	Not available.		
Evaporation Rate	<1 compared to Water		
Dispersion Properties	See solubility in water.		
Solubility	Easily soluble in cold water.		
The Product is:	Non-flammable.		
Auto-ignition Temperature	Not available.		
Flash Points	Not available.		
Flammable Limits	Not available.		
Fire Hazards in Presence of Various Substances	No specific information is available in our database regarding the flammability of this product in presence of various materials.		
Explosion Hazards in Presence of Various Substances	Not applicable		

Section 10. Stability and Reactivity Data

Stability	The product is stable.
Incompatibility with Various Substances	Strong acids. acids
Hazardous Decomposition Products	not available

Section 11. Toxicological Information

Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol). Acute toxicity of the gas (LC50): 926 ppm 4 hour(s) [Mouse]. (2-Butoxyethanol).
Acute Effects on Humans	<i>Eyes</i> Corrosive to the eyes. <i>Skin</i> Severe skin irritant. May cause moderate reddening, swelling, and possible skin damage. Causes Severe Skin Burns (EU). <i>Inhalation</i> Harmful if inhaled. <i>Ingestion</i> Irritating to mouth, throat and stomach. May cause headache, dizziness, nausea, vomiting and diarrhea.
Chronic Effects on Humans	Prolonged exposure may result in skin burns and ulcerations. Severe over-exposure can produce lung damage, choking, unconsciousness or death. The amount of tissue damage depends on length of contact.
Special Remarks on Toxicity to Animals	No additional remark.
Special Remarks on Chronic Effects on Humans	No additional remark.

Section 12. Ecological Information

Ecotoxicity	Not available.
BOD5 and COD	Will Not Occur
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.
Toxicity of the Products of Biodegradation	Not available.
Special Remarks on the Products of Biodegradation	No additional remark.

Section 13. Disposal Considerations

Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Waste Stream	Not available.

Section 14. Transport Information

DOT (U.S.A)
(Pictograms)



TDG Classification

8



PIN UN, Proper Shipping Name: Corrosive liquids n.o.s. UNNA: UN1760 PG: II
Name, PG

Maritime Transportation Not available.

Special Provisions for Transport Not available.

Section 15. Other Regulatory Information and Pictograms

WHMIS (Classification) E



Regulatory Lists No products were found.

Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications

HCS (U.S.A.) HCS CLASS: Toxic.
HCS CLASS: Corrosive liquid.

USA Regulatory Lists

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Butoxyethanol: immediate health hazard, delayed health hazard
SARA 313 toxic chemical notification and release reporting: 2-Butoxyethanol


DSD (EEC) This product is not classified according to the EU regulations.

International Regulations Lists No products were found.

Hazardous Material Information System (U.S.A.)

Health	3
Flammability	0
Physical Hazard	0

National Fire Protection Association (U.S.A.)



The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product. **Specific Hazard**

Section 16. Other Information

Validated by CRushton on 2/13/2009.

Verified by CRushton.

Printed 2/13/2009.

Information Contact Betco Corporation
1001 Brown Avenue
Toledo, Ohio 43607

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Continued on Next Page