



2000 - 3000 sq. ft./gallon

# GLARE®



## Metal Interlocked Acrylic Polymer Floor Finish

This brilliant, high gloss floor finish will give your floors an appearance that everyone will stop and admire! Setting the standard for today's modern floor coverings, this acrylic, thermo-plastic finish provides the optimum in durability and wear. Essentially a nonbuff formula, it is easily maintained using a variety of maintenance procedures including spray buff and mop-on restorers. Designed with superior leveling properties, it is easy to apply and flows smoothly for the ultimate in gloss. This finish has excellent slip resistant qualities and is easily removed with either conventional or no-rinse strippers.

### Uses

- Resilient tile
- Terrazzo
- Linoleum

### Benefits

- Durability – Extended wear and superior protection for your floor covering.
- Appearance – High gloss as well as black mark and detergent resistant. Never yellows for cleaner, brighter-looking floors.
- Ease – Self-leveling, excellent flow for easy application with little or no mop drag. May be used with or without floor sealer.
- Versatile – For use on all resilient flooring as well as terrazzo and some hard tile surfaces.

### Properties

Coverage.....	2,000 - 3,000 square feet/gallon
Drying time.....	20 - 30 minutes
Freeze/thaw stability .....	3 cycles
Fragrance.....	Mild
Gloss (ASTM D 1455-87).....	1. coat 75 - 80
	2 coats 85 - 90
Heel mark resistance.....	Very good
Leveling .....	Excellent
Solids.....	>18%
pH.....	8.1 - 8.9
Recoat.....	Excellent
Shelf life .....	1 year
Specific gravity .....	1.02



CLASSIFIED BY:  
Underwriters Laboratories Inc.®  
AS TO SLIP RESISTANCE ONLY.  
2N39

Authorized Betco Distributor



### Directions For Use

#### Read the entire label before using this product.

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures and humidity may extend dry time. 4 - 5 coats of finish are recommended. **Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.** ROUTINE MAINTENANCE: Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating. INTERIM MAINTENANCE: Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. **Note: Slip resistance meets or exceeds standard, (ASTM D 2047-04) James Machine 0.5 minimum.**

### Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION:** Contains emulsifiers. Avoid contact with skin and eyes. Harmful if swallowed. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician.

### Available In

Case/4 - 1 Gallon (3.78 L): Item #60504-00  
Pail/5 Gallon (18.9 L): Item #60505-00  
Drum/55 Gallon (208 L): Item #60555-00

Literature Item #60592-92

C1010 - Floor Care - Finishes

07.06



The Cleaning Edge™