



Ready-To-Use

# GREEN EARTH® PRELUDE™ FLOOR FINISH AND SEALER



Provides an environmentally preferred solution for protecting and maintaining floors. This versatile and durable sealer and finish can be used with all types of maintenance programs including both low and high speed.

This product is part of Betco's Green Earth® program. Betco's Green Earth® products are formulated and packaged to have a reduced environmental impact while still maintaining superior performance. Please dispose of this product and waste generated from this product in accordance with all applicable local, state, and Federal regulations.



### Uses

- Resilient tile

### Maintenance

- Moderate burnishing
- Low/high speed compatible

### Performance Benefits

- High gloss.
- Extended wear formula.
- Holds gloss between burnishing.
- Use as a sealer or a finish.
- Excellent leveling.
- Excellent adhesion properties.

### \*Environmental Benefits

- No zinc crosslinking agents.
- Less than 0.5% total phosphorous
- No ammonia.
- No flammable solvents.
- No 2-Butoxyethanol.
- No environmentally toxic preservatives.
- No alkyl phenol ethoxylate (APE).
- No bio-accumulative fluorocarbon surfactants.
- No added fragrance.
- VOC's do not exceed established limits for applicable category.
- Low environmental impact packaging.

### Properties

Color (dried).....	Crystal Clear
Color (liquid).....	White
Coverage.....	2000 - 3000 square feet/gallon
Drying time.....	30 - 40 minutes per coat
Fragrance.....	Mild
Freeze/thaw stability.....	3 cycles
Gloss (ASTM D1455) One Coat.....	80 - 85
Five Coats.....	90 - 95
Heel mark resistance.....	Very good
Leveling.....	Excellent
pH.....	7.0 - 8.5
Powdering resistance.....	Excellent
Shelf life.....	1 year
Solids.....	> 18%
Specific Gravity.....	1.03

### Directions For Use

Read the entire label before using this product.

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 30 - 40 minutes. 4 - 5 coats of finish are recommended. **Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.** ROUTINE MAINTENANCE: Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating. INTERIM MAINTENANCE: Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. **Note: Slip resistance meets or exceeds (ASTM D 2047-93) James Machine 0.5 minimum.** Please dispose of this product and waste generated from this product in accordance with all applicable local, state, and Federal regulations.

### Safety

**SAFETY:** CAUTION: Eye irritant. May cause skin irritation. May cause respiratory irritation. Wear safety glasses, and gloves. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If swallowed, drink two glasses of water. Call a physician. If inhaled, remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration, preferably mouth-to-mouth. Do not induce vomiting unless instructed to do so by poison control center or doctor.

### Available In

Case/4 - 1 Gallon (3.78L): Item #54704-00  
 BIB/5 Gallon (18.9 L): Item #54739-00

Literature Item #54792-92

Authorized Betco Distributor

C3100 - Green Earth Program

04.08



The Cleaning Edge™

©Betco Corporation • All Rights Reserved • 1001 Brown Avenue • Toledo, Ohio 43607-0127 • 888-GO BETCO (888-462-3826) • email@betco.com • www.betco.com